

# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 650/65 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	650	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1710	<b>RIM ALT</b>	DW 20 B
<b>SLR (MM)</b>	764	<b>ECE</b>	E4-106R-001826
<b>RC (MM)</b>	5078	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2355	2775	3150	3535	3870	4205
<b>FROM 65 TO 40</b>	2590	3050	3465	3885	4255	4625
30	2690	3170	3600	4040	4425	4810
20	2795	3290	3740	4195	4595	4995
10	3285	3870	4400	4930	5400	5870
<b>UPTO 30 CYC</b>	3365	3965	4500	5050	5530	6010
<b>UPTO 15 CYC</b>	4010	4725	5370	6020	6595	7165
<b>UPTO 10 CYC</b>	4400	5185	5890	6600	7230	7860
10HT	2690	3170	3600	4040	4425	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.