


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 157 D ; 160 A8 |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1644 | RIM ALT | W 18 L |
| SLR (MM) | 742 | ECE | E4-106R-001405 |
| RC (MM) | 4960 | SRI | 775 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 1980 | 2310 | 2600 | 2890 | 3180 | 3425 | 3795 | 4125 |
| 50 | 2085 | 2430 | 2735 | 3035 | 3340 | 3600 | 3990 | 4335 |
| 40 | 2160 | 2520 | 2835 | 3150 | 3465 | 3735 | 4140 | 4500 |
| 30 | 2280 | 2660 | 2990 | 3325 | 3655 | 3940 | 4370 | 4745 |
| 10 LT | 2655 | 3100 | 3485 | 3875 | 4260 | 4590 | 5090 | 5530 |
| 10 HT | 2280 | 2660 | 2990 | 3325 | 3655 | 3940 | 4370 | 4745 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.