

AGRIMAX FORCE

TIRE SIZE	IF 710/75 R 42 CFO
UM	IS STANDARD
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	181 D

DIMENSIONES IS STANDARD

SW (MM)	716	RIM REC	DW 25 B
OD (MM)	2133	RIM ALT	DW 23 B
SLR (MM)	967	ECE	E11-106R-006490
RC (MM)	6403	SRI	1000

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3525	4050	4650	5255	5855	6455	7055	7505
FROM 65 TO 40	3875	4455	5115	5775	6435	7095	7755	8250
30	4030	4630	5315	6005	6690	7375	8065	8580
20	4185	4810	5520	6235	6945	7660	8375	8910
10	4920	5655	6495	7330	8170	9010	9845	10475
UPTO 30 CYC	5035	5790	6645	7505	8365	9220	10080	10725
UPTO 15 CYC	6005	6905	7925	8950	9970	10995	12020	12785
UPTO 10 CYC	6585	7570	8695	9815	10935	12060	13180	14025
10 HT	4030	4630	5315	6005	6690	7375	8065	8580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

