

FLOTATION TR 675

TIRE SIZE	500/60 - 22.5
UM	US STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B



DIMENSIUNI US STANDARD

USA CODE	94019786	RC (IN)	141.9
SW (IN)	20.3	RIM REC	AG 16.00
OD (IN)	46.5	RIM ALT	15.00; 17.00
SLR (IN)	21.3	ECE	E4-106R-002314

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	35
5 FR	9680	11450	12730
10 FR	8710	10310	11460
20 FR	7740	9160	10180
25 FR	6910	8180	9090
30 FR	6220	7360	8270
5 DW	6800	8040	8950
10 DW	6130	7230	8060
20 DW	5450	6440	7160
25 DW	4860	5740	6390
30 DW	4380	5170	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.