

AS 504

TIRE SIZE	24X8.50 - 12
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	81 A8
LI/SS FREE ROLLING	94 A8



РАЗМЕРЫ US STANDARD

USA CODE	94512409	RC (IN)	69.3
SW (IN)	8.5	RIM REC	7 JA; 7.00 I
OD (IN)	24.0	ECE	E11-106R-0010452
SLR (IN)	11.2	PR	6

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	74
5 FR	2070
15 FR	1750
20 FR	1650
25 FR	1480
5 DW	1420
15 DW	1215
20 DW	1140
25 DW	1020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.