

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 500/50 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 146 A8/142 B |
| LI/SS FREE ROLLING | 158 A8/155 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94006335 | RC (IN) | 126.0 |
| SW (IN) | 19.7 | RIM REC | AG 16.00 |
| OD (IN) | 42.1 | ECE | E4-106R-001560 |
| SLR (IN) | 18.7 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 38 | 41 | 44 |
|-----------|-------|-------|-------|
| 5 FR | 12070 | 12590 | 13120 |
| 10 FR | 10860 | 11330 | 11810 |
| 20 FR | 9660 | 10070 | 10490 |
| 25 FR | 8620 | 8990 | 9370 |
| 30 FR | 7760 | 8090 | 8540 |
| 5 DW | 8520 | 8880 | 9260 |
| 10 DW | 7670 | 8000 | 8330 |
| 20 DW | 6810 | 7110 | 7410 |
| 25 DW | 6080 | 6350 | 6610 |
| 30 DW | 5480 | 5710 | 5840 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.