


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/80 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94053766	<b>RC (IN)</b>	210.9
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	71.0	<b>RIM ALT</b>	W 15 L ; DW 16 L
<b>SLR (IN)</b>	32.3	<b>ECE</b>	E11-106R-002991

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	3950	4590	5240	5870	6530	7160
<b>25</b>	3950	4590	5240	5870	6530	7160
<b>20</b>	4220	4920	5610	6290	6990	7670
<b>5 LT</b>	5290	6150	7010	7880	8740	9600
<b>5 HT</b>	4220	4920	5610	6290	6990	7670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.