


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 480/80 R 42</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR DE ALTA POTENCIA /<br>TRACTOR  |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONES IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 479  | <b>RIM REC</b> | DW 16 L          |
| <b>OD (MM)</b>  | 1840 | <b>RIM ALT</b> | DW 15 L          |
| <b>SLR (MM)</b> | 826  | <b>ECE</b>     | E11-106R-0010410 |
| <b>RC (MM)</b>  | 5465 | <b>SRI</b>     | 875              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  | 2    | 2.4  |
|----------------------|------|------|------|------|------|------|------|------|
| 70                   | 2395 | 2755 | 3160 | 3570 | 3975 | 4385 | 4790 | 5095 |
| <b>FROM 65 TO 40</b> | 2635 | 3025 | 3475 | 3920 | 4370 | 4820 | 5265 | 5600 |
| 30                   | 2685 | 3085 | 3545 | 4000 | 4455 | 4915 | 5370 | 5710 |
| 20                   | 2740 | 3145 | 3610 | 4075 | 4540 | 5010 | 5475 | 5820 |
| 10                   | 2900 | 3330 | 3820 | 4315 | 4805 | 5300 | 5795 | 6160 |
| <b>UPTO 10 CYC</b>   | 3910 | 4495 | 5160 | 5825 | 6490 | 7155 | 7820 | 8315 |
| 10HT                 | 2685 | 3085 | 3545 | 4000 | 4455 | 4915 | 5370 | 5710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.