


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 600/65 R 34 NRO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94070275	<b>RC (IN)</b>	195.0
<b>SW (IN)</b>	23.5	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	64.7	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	28.8	<b>ECE</b>	E11-106R-007603

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5360	6170	7100	7910	8840	9660	10820	11630
<b>FROM 40 TO 25</b>	5890	6780	7800	8700	9720	10610	11890	12790
20	6010	6910	7960	8870	9920	10820	12140	13040
12	6120	7050	8110	9050	10110	11030	12370	13290
5	6470	7460	8590	9570	10690	11680	13080	14060
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8240	9490	10920	12180	13610	14860	16650	17900
5 HT	6010	6910	7960	8870	9920	10820	12140	13040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.