

# AW 705

<b>TIRE SIZE</b>	<b>15.0/70 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	151 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94025749	<b>RC (IN)</b>	121.7
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	39.8	<b>RIM ALT</b>	13; W 13
<b>SLR (IN)</b>	17.6	<b>ECE</b>	E4-106R-002266

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>62</b>
<b>5 FR</b>	10650
<b>15 FR</b>	9050
<b>20 FR</b>	8520
<b>25 FR</b>	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.