

# COLT

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 7.50 - 15                                       |
| <b>UM</b>           | IS STANDARD                                     |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | LIGHT TRUCK / TRAILER /<br>IMPLEMENTS / TRAILER |
| <b>VERSION</b>      | STANDARD  |
| <b>TL/TT</b>        | TT  |



## DIMENSIONS IS STANDARD

|                 |     |                |      |
|-----------------|-----|----------------|------|
| <b>SW (MM)</b>  | 217 | <b>RIM REC</b> | 6.00 |
| <b>OD (MM)</b>  | 790 | <b>PR</b>      | 14   |
| <b>SLR (MM)</b> | 0   |                |      |
| <b>RC (MM)</b>  | 0   |                |      |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.50</b> |
| <b>100 LS</b>     | 1450        |
| <b>100 LD</b>     | 1375        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.