


# RIDEMAX FL 693 M



<b>TYRE SIZE</b>	<b>VF 400/45 R 17.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	142 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	14.00
<b>OD (MM)</b>	800	<b>ECE</b>	E11-106R-007199
<b>SLR (MM)</b>	357	<b>SRI</b>	390
<b>RC (MM)</b>	2448		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.2	1.6	2	2.4	2.8	3.2	3.6	4.0
70	1040	1260	1405	1620	1840	2005	2200	2415
65	1140	1380	1540	1780	2015	2200	2415	2650
50	1385	1670	1865	2155	2440	2665	2925	3210
40	1555	1875	2095	2420	2740	2995	3285	3605
30	1725	2085	2325	2685	3045	3325	3645	4005
25	1805	2180	2435	2810	3185	3480	3815	4190
10	2055	2485	2770	3200	3630	3960	4345	4770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.