


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94045358	<b>RC (IN)</b>	243.4
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	80.2	<b>RIM ALT</b>	DW 15 L; W 15 L
<b>SLR (IN)</b>	37.2	<b>ECE</b>	E4-106R-001495

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58	64	73
<b>30</b>	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
<b>25</b>	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
<b>20</b>	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750
<b>5 LT</b>	6080	6990	8020	9060	10090	11120	12030	12930	14060	15320	16160	17210	18670	20980
<b>5 HT</b>	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.