


AGRIMAX SPARGO

TIRE SIZE	VF 480/80 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	176 D



DIMENSIONES US STANDARD

CÓDIGO USA	94075317	RC (IN)	219.4
SW (IN)	18.9	RIM REC	DW 16 L
OD (IN)	72.2	RIM ALT	DW 15 L
SLR (IN)	33.0	ECE	E11-106R-009072

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8110	8980	9850	10280	10860	11150	11440	12020	12600	13030	13610	14050	14480
FROM 40 TO 25	8770	9720	10640	11120	11740	12060	12370	12990	13630	14090	14720	15190	15660
20	8940	9910	10860	11350	11990	12310	12630	13250	13900	14390	15020	15500	15980
12	9120	10100	11070	11570	12220	12550	12870	13520	14170	14660	15300	15800	16290
5*	9650	10690	11710	12230	12920	13270	13610	14290	14980	15500	16190	16700	17220
UPTO 20 CYCLIC	9960	11030	12090	12610	13330	13690	14050	14750	15470	16000	16700	17240	17770
UPTO 10 CYCLIC	11890	13170	14420	15060	15920	16340	16770	17610	18470	19110	19940	20580	21220
UPTO 5 CYCLIC	13150	14570	15970	16680	17630	18090	18560	19490	20440	21150	22080	22790	23490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.