DATA SHEET

PRINTED ON
23-04-2026

AS 504

TIRE SIZE	**16.5/85 - 24**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	155 A8
LI/SS FREE ROLLING	168 A8

DIMENSÕES IS STANDARD

SW (MM)	415	**RIM REC**	W 13
OD (MM)	1325	**RIM ALT**	W 14 L; W 15 L
SLR (MM)	584	**ECE**	E4-106R-001877
RC (MM)	4013	**PR**	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80
10 FR	7840
25 FR	6665
30 FR	6270
40 FR	5600
10 DW	5425
25 DW	4610
30 DW	4340
40 DW	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..