

RIDEMAX FL 615

TIRE SIZE	800/65 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	REMORCĂ / CISTERNĂ / MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	185 D



DIMENSIUNI US STANDARD

USA CODE	94070176	RC (IN)	221.4
SW (IN)	32.7	RIM REC	DW 27 B
OD (IN)	73.0	ECE	E11-106R-007528
SLR (IN)	32.8		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	87
40	8770	9590	11630	12850	14890	16930	18560	20390
30	10610	11610	14080	15550	18020	20490	22460	24680
25	11930	13040	15820	17480	20250	23030	25240	27730
20	13250	14480	17560	19410	22490	25570	28030	30800
15	13860	15140	18370	20300	23520	26750	29320	32220
5	15780	17260	20930	23130	26800	30470	33410	36700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.