

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>12.5/80 - 15.3</b>  |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | EMPACADORA DE HENO /<br>MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ COSECHADORA / MAQUINARIA<br>AGRÍCOLA |
| <b>VERSIÓN</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 142 A8   |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94010721 | <b>RC (IN)</b> | 102.1           |
| <b>SW (IN)</b>    | 12.3     | <b>RIM REC</b> | 9.00            |
| <b>OD (IN)</b>    | 35.0     | <b>ECE</b>     | E11-106R-003602 |
| <b>SLR (IN)</b>   | 15.2     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>62</b> |
|------------------|-----------|
| 5 FR             | 8180      |
| 15 FR            | 6960      |
| 20 FR            | 6550      |
| 25 FR            | 5840      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.