


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 480/80 R 38 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 166 A8 ; 161 D |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1733 | RIM ALT | W 16 L |
| SLR (MM) | 780 | ECE | E11-106R-004075 |
| RC (MM) | 5213 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 2175 | 2685 | 3145 | 3655 | 4115 | 4625 |
| 50 | 2350 | 2900 | 3400 | 3950 | 4450 | 5000 |
| 40 | 2490 | 3075 | 3605 | 4185 | 4715 | 5300 |
| 30 | 2595 | 3200 | 3755 | 4360 | 4915 | 5520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.