


EARTHMAX SR 454

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TYRE SIZE | 33.00 R 51 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | RIGID DUMP TRUCK |
| VERSION | HEAT RESISTANT COMPOUND |
| TYRE TYPE | TL |
| LI/SS | 235 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-----------|--------------------|----|
| OD (MM) | 2990 | TRA CODE | E3 |
| SLR (MM) | 1358 | STAR RATING | ★★ |
| RC (MM) | 9085 | | |
| RIM REC | 24.00/5.0 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 30000 | 30750 | 32500 | 33500 | 34500 | 35500 | 36500 | 37500 | 38750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.