

# AT 316

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>24X12.00 - 12</b>                                    |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | КОМПАКТНЫЙ ТРАКТОР ОБЩЕГО<br>НАЗНАЧЕНИЯ / ТРАКТОР-ТЯГАЧ |
| <b>VERSION</b>      | ARAMID BELTED   |
| <b>TIRE TYPE</b>    | TL  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                              |
|-----------------|------|----------------|------------------------------|
| <b>SW (MM)</b>  | 315  | <b>RIM REC</b> | 10.50   - 55;   - 70;   - 90 |
| <b>OD (MM)</b>  | 610  | <b>PR</b>      | 6                            |
| <b>SLR (MM)</b> | 271  |                |                              |
| <b>RC (MM)</b>  | 1769 |                |                              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.20</b> |
| 15                | 1030        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.