


# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>580/70 R 38</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | IRRORAZIONE / TRATTORE /<br>VENDEMMIATRICE / MIETITREBBIA /<br>ATTREZZI AGRICOLI         |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 155 D  |



## DIMENSIONI US STANDARD

|                   |          |                 |                 |
|-------------------|----------|-----------------|-----------------|
| <b>CODICE USA</b> | 94062249 | <b>RC (IN)</b>  | 215.4           |
| <b>SW (IN)</b>    | 22.7     | <b>RIM REC</b>  | W 18 L          |
| <b>OD (IN)</b>    | 71.9     | <b>ECE</b>      | E11-106R-005526 |
| <b>SLR (IN)</b>   | 32.3     | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20    | 23    |
|-----------|------|------|------|------|-------|-------|
| 40        | 4710 | 5470 | 6240 | 7010 | 7780  | 8540  |
| 30        | 4940 | 5740 | 6560 | 7360 | 8170  | 8970  |
| 25        | 5150 | 6000 | 6830 | 7680 | 8520  | 9360  |
| 20        | 5410 | 6290 | 7190 | 8070 | 8950  | 9830  |
| 5 LT      | 6300 | 7330 | 8370 | 9390 | 10430 | 11450 |
| 5 HT      | 5410 | 6290 | 7190 | 8070 | 8950  | 9830  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.