

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8/144 B
<b>LI/SS FREE ROLLING</b>	160 A8/156 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94019809	<b>RC (IN)</b>	143.3
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	49.6	<b>ECE</b>	E11-106R-004396
<b>SLR (IN)</b>	21.5	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	30
<b>5 FR</b>	11410	12690	13890
<b>10 FR</b>	10260	11420	12500
<b>20 FR</b>	9130	10150	11110
<b>25 FR</b>	8150	9060	9920
<b>30 FR</b>	7330	8160	8820
<b>5 DW</b>	7980	8880	9720
<b>10 DW</b>	7180	8000	8750
<b>20 DW</b>	6380	7110	7780
<b>25 DW</b>	5700	6350	6940
<b>30 DW</b>	5130	5710	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.