

AGRIMAX RT 855

| | |
|---------------------|---|
| TIRE SIZE | 380/85 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 139 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 380 | RIM REC | W 12 |
| OD (MM) | 1611 | RIM ALT | W 11 ; W 13 |
| SLR (MM) | 736 | ECE | E4-106R-000660 |
| RC (MM) | 4842 | SRI | 775 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| 40 | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| 30 | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |
| 10 LT | 1795 | 2090 | 2380 | 2675 | 2970 | 3260 |
| 10 HT | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.