

FLOTATION 648 T



| | |
|---------------------------|----------------------|
| TIRE SIZE | 550/45 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | КОМБАЙН / КОМБАЙН |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 154 A8/150 B |
| LI/SS FREE ROLLING | 166 A8/162 B |

РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 550 | RIM REC | AG 16.00 |
| OD (MM) | 1070 | ECE | E4-106R-002046 |
| SLR (MM) | 475 | PR | 20 |
| RC (MM) | 3203 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.00 | 3.50 | 4.00 |
|------------|------|------|------|
| 10 FR | 6270 | 6860 | 7420 |
| 20 FR | 5645 | 6175 | 6680 |
| 30 FR | 5020 | 5490 | 5935 |
| 40 FR | 4480 | 4900 | 5300 |
| 50 FR | 4030 | 4410 | 4750 |
| 10 DW | 4440 | 4860 | 5250 |
| 20 DW | 3995 | 4370 | 4725 |
| 30 DW | 3550 | 3885 | 4200 |
| 40 DW | 3170 | 3470 | 3750 |
| 50 DW | 2855 | 3125 | 3350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.