


# AS 504

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	134 A8
<b>LI/SS FREE ROLLING</b>	147 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	465	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	865	<b>ECE</b>	E11-106R-006179
<b>SLR (MM)</b>	389	<b>PR</b>	16
<b>RC (MM)</b>	2578	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	4305
25 FR	3660
30 FR	3445
40 FR	3075
10 DW	2970
25 DW	2525
30 DW	2375
40 DW	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.