


# AW 711

**15 R 19.5**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / UYGULAMALI MAKINE / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
	139 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	389	<b>RIM REC</b>	11.75
<b>OD (MM)</b>	1019	<b>RIM ALT</b>	12.75
<b>SLR (MM)</b>	471	<b>ECE</b>	E11-106R-006649
<b>RC (MM)</b>	3094	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	5.5
65	660	855	1045	1170	1365	1535	1705	1850	2045	2285	2430
50	840	1090	1340	1495	1745	1960	2180	2365	2615	2925	3110
40	885	1145	1405	1565	1830	2055	2285	2480	2740	3065	3260
25	960	1245	1530	1710	1995	2240	2490	2705	2990	3345	3555
10	1335	1730	2125	2370	2765	3110	3455	3755	4150	4640	4935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.