


FLOTATION 648

TIRE SIZE	550/60 - 22.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/152 B
LI/SS FREE ROLLING	169 A8/165 B



DIMENSIONES US STANDARD

CÓDIGO USA	94045327	RC (IN)	146.7
SW (IN)	21.7	RIM REC	AG 16.00
OD (IN)	48.8	ECE	E4-106R-001565
SLR (IN)	21.3	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
5 FR	17240	17580	17900
10 FR	15510	15820	16110
20 FR	13790	14060	14320
25 FR	12310	12550	12790
30 FR	11080	11300	11350
5 DW	11880	12110	12350
10 DW	10690	10900	11110
20 DW	9500	9690	9880
25 DW	8490	8650	8820
30 DW	7640	7790	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.