

# AW 705

<b>TIRE SIZE</b>	16.0/70 - 20
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	151 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	408	<b>RIM REC</b>	13.0
<b>OD (MM)</b>	1075	<b>RIM ALT</b>	12 SDC; 13 SDC; 14
<b>SLR (MM)</b>	480	<b>ECE</b>	E4-106R-002711
<b>RC (MM)</b>	3155	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.00</b>
10 FR	4830
25 FR	4105
30 FR	3865
40 FR	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.