


AGRIMAX SIRIO

TIRE SIZE	540/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	HIGH SPEED
TIRE TYPE	TL
LI/SS	153 D ; 150 E



РАЗМЕРЫ US STANDARD

USA CODE	94044290	RC (IN)	198.8
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	65.6	RIM ALT	W 18 L
SLR (IN)	30.3	ECE	E4-106R-000816

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	3470	3990	4590	5170	5760	6360	6880	7390
40	3790	4350	4990	5630	6280	6920	7480	8050
30	3980	4570	5250	5920	6600	7270	7870	8450
25	4140	4760	5470	6170	6880	7580	8200	8820
15	4500	5160	5920	6690	7450	8210	8880	9550
5	5680	6530	7480	8450	9420	10380	11230	12070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.