

# EARTHMAX SR 49 M

|                  |                                                                             |
|------------------|-----------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>29.5 R 25</b>                                                            |
| <b>UM</b>        | US STANDARD                                                                 |
| <b>MACHINERY</b> | DOZER / LOAD HAUL DUMP (LHD) /<br>LOADER / LOW PROFILE DUMP TRUCK<br>(LPDT) |
| <b>VERSION</b>   | CUT RESISTANT COMPOUND                                                      |
| <b>TL/TT</b>     | TL                                                                          |

## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94067947 | <b>RIM REC</b>     | 25.00/3.5 |
| <b>OD (IN)</b>  | 75.0     | <b>TRA CODE</b>    | E4/L4     |
| <b>SLR (IN)</b> | 33.2     | <b>STAR RATING</b> | ★★★★/★★★  |
| <b>RC (IN)</b>  | 220.5    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

