


AGRIMAX RT 945

| | |
|---------------------|--|
| TIRE SIZE | 380/90 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / TRAKTOR / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94021833 | RC (IN) | 224.4 |
| SW (IN) | 15.0 | RIM REC | W 12 |
| OD (IN) | 72.9 | RIM ALT | W 11 ; W 13 |
| SLR (IN) | 33.8 | ECE | E4-106R-001409 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 64 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 30 | 3940 | 5050 | 6150 | 6760 | 7260 | 7950 | 8540 | 8970 | 9640 | - |
| 25 | 3940 | 5050 | 6150 | 6760 | 7260 | 7950 | 8540 | 8970 | 9640 | - |
| 20 | 4210 | 5400 | 6590 | 7230 | 7780 | 8510 | 9150 | 9610 | 10330 | - |
| 5 | 4620 | 6030 | 7310 | 8720 | 10010 | 10390 | 11540 | 12820 | 13320 | 14470 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.