


# BK 826

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>8.25 - 16</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS / HARVESTER<br>/ TRAILER / BACKHOE LOADER                         |
| <b>VERSION</b>      | TRACTOR TRAILER  |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 134 A8   |



## DIMENSIONS IS STANDARD

|                |        |           |    |
|----------------|--------|-----------|----|
| <b>SW (MM)</b> | 238    | <b>PR</b> | 16 |
| <b>OD (MM)</b> | 863    |           |    |
| <b>RIM REC</b> | 6.50 H |           |    |
| <b>RIM ALT</b> | 6.00 G |           |    |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.60</b> |
| 40                | 2120        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.