



PRINTED ON  
23-04-2026

## DATA SHEET

# FS 216

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | <b>18.4 - 34</b>       |
| <b>UM</b>           | US STANDARD            |
| <b>CONSTRUCTION</b> |                        |
| <b>MACHINERY</b>    | LOG SKIDDER / FORESTRY |
| <b>VERSION</b>      | STEEL BELTED           |
| <b>TIRE TYPE</b>    | TT                     |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94028122 | <b>RC (IN)</b> | 198.5           |
| <b>SW (IN)</b>  | 18.4     | <b>RIM REC</b> | DW 16 A         |
| <b>OD (IN)</b>  | 66.1     | <b>ECE</b>     | E11-106R-004560 |
| <b>SLR (IN)</b> | 30.2     | <b>PR</b>      | 10              |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>30</b> | <b>25</b> |
|------------------|-----------|-----------|
| 5                | 8950      | -         |
| 20               | -         | 6400      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.