


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 600/60 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	595	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1485	<b>RIM ALT</b>	DW 18 L; DW 21 B
<b>SLR (MM)</b>	649	<b>ECE</b>	E11-106R-002979
<b>RC (MM)</b>	4404	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2120	2475	2820	3170	3515	3865
<b>FROM 65 TO 40</b>	2335	2720	3100	3485	3865	4250
30	2380	2770	3160	3550	3940	4335
20	2425	2825	3220	3620	4015	4420
10	2565	2990	3410	3830	4250	4675
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3270	3805	4340	4875	5410	5950
10HT	2380	2770	3160	3550	3940	4335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.