


AGRIMAX V- FLECTO

VF 900/65 R 46

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| | 193 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 900 | RIM REC | DW 30B |
| OD (MM) | 2338 | ECE | E11-106R-0010961 |
| SLR (MM) | 1006 | SRI | 1100 |
| RC (MM) | 7003 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|-------|-------|-------|-------|-------|
| 70 | 5335 | 6170 | 7010 | 7950 | 8685 | 9415 | 10465 |
| FROM 65 TO 40 | 5865 | 6785 | 7705 | 8740 | 9545 | 10350 | 11500 |
| 30 | 5980 | 6920 | 7855 | 8910 | 9735 | 10555 | 11730 |
| 20 | 6095 | 7055 | 8010 | 9085 | 9925 | 10760 | 11960 |
| 10 | 6450 | 7460 | 8475 | 9610 | 10495 | 11385 | 12650 |
| *UPTO 10 CYC WITH FRONT LOADER | 8215 | 9500 | 10790 | 12240 | 13365 | 14490 | 16100 |
| 10HT | 5980 | 6920 | 7855 | 8910 | 9735 | 10555 | 11730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.