DATA SHEET

PRINTED ON
23-04-2026

MULTIMAX MP 569

TIRE SIZE	**445/70 R 19.5**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	ÎNCĂRCĂTOR TELESCOPIC / EXCAVATOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 A8 ; 180 A2

DIMENSIUNI IS STANDARD

OD (MM)	1112	**ECE**	E11-106R-0011615
SLR (MM)	498		
RC (MM)	3363		
RIM REC	14.00		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	7.50
10	8000
40	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..