


# FARM SPECIAL

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>18.4 - 30</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 139 A6   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 451  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1533 | <b>RIM ALT</b> | W 15 L          |
| <b>SLR (MM)</b> | 689  | <b>ECE</b>     | E11-106R-005537 |
| <b>RC (MM)</b>  | 4599 | <b>PR</b>      | 8               |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.40</b> |
| 30                | 2430        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.