

# AS 504

**7.50 - 16**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	TELESKOPIK YÜKLEYİCİ / TARLA RÖMORKU / UYGULAMALI MAKİNE / TELESKOPIK YÜKLEYİCİ
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TT
	99 A8
	112 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94043026	<b>RC (IN)</b>	97.4
<b>SW (IN)</b>	8.2	<b>RIM REC</b>	5.50 F
<b>OD (IN)</b>	31.6	<b>RIM ALT</b>	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
<b>SLR (IN)</b>	14.6	<b>ECE</b>	E11-106R-004337

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	3460
15 FR	2940
20 FR	2770
25 FR	2470
5 DW	2390
15 DW	2030
20 DW	1920
25 DW	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.