

# AS 504

<b>TIRE SIZE</b>	<b>9.0/70 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	106 A8
<b>LI/SS FREE ROLLING</b>	119 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	222	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	760	<b>ECE</b>	E11-106R-004536
<b>SLR (MM)</b>	355	<b>PR</b>	10
<b>RC (MM)</b>	2285		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.40
10 FR	1905
25 FR	1620
30 FR	1525
40 FR	1360
10 DW	1330
25 DW	1130
30 DW	1065
40 DW	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.