


# RIB 900

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>400/60 - 15.5</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS                               |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>ATTREZZI AGRICOLI / RIMORCHIO /<br>MIETITREBBIA / MIETITREBBIA /<br>ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 139 A8   |



## DIMENSIONI IS STANDARD

|                 |      |                |          |
|-----------------|------|----------------|----------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | AG 13.00 |
| <b>OD (MM)</b>  | 875  | <b>PR</b>      | 10       |
| <b>SLR (MM)</b> | 380  |                |          |
| <b>RC (MM)</b>  | 2564 |                |          |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.50</b> |
|-------------------|-------------|
| 10 FR             | 3135        |
| 25 FR             | 2665        |
| 30 FR             | 2510        |
| 40 FR             | 2240        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.