

RIDEMAX FROST

TIRE SIZE	440/80 R 28 IND
UM	US STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	156 A8 ; 151 D



DIMENSIONS US STANDARD

USA CODE	94513338	RC (IN)	169.1
SW (IN)	17.4	RIM REC	DW 14 L
OD (IN)	55.9	RIM ALT	DW 15 L
SLR (IN)	25.3	ECE	E11-106R-0010949

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	38	41	44	46
45	3350	4420	5320	5860	6240	6550	6840	7230	7610
30	3630	4770	5760	6340	6750	7080	7410	7810	8220
25	3880	5110	6170	6790	7230	7580	7940	8380	8820
20	4020	5300	6390	7030	7480	7860	8220	8670	9130
10	4220	5570	6710	7390	7870	8260	8630	9120	9590
5	4830	6360	7670	8440	8990	9420	9870	10420	10960
3	5600	7370	8910	9790	10430	10930	11440	12080	12710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.