



Latest update  
2-06-2026

## DATA SHEET

# TR 678

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>780/50 - 28.5</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | IMPLEMENT MACHINERY / TRAILER /<br>IMPLEMENTS / FORESTRY /<br>EXCAVATOR / TRAILER |
| <b>VERSION</b>      | STEEL BELTED  |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 190 A2 ; 182 A8   |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94068982 | <b>RC (IN)</b> | 182.8           |
| <b>SW (IN)</b>  | 30.3     | <b>RIM REC</b> | AG 26.00        |
| <b>OD (IN)</b>  | 59.6     | <b>ECE</b>     | E11-106R-006975 |
| <b>SLR (IN)</b> | 27.6     | <b>PR</b>      | 24              |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 87    |
|-----------|-------|
| 25        | 18740 |
| 5         | 23370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.