



US standard



GROWING TOGETHER

AIROMAX

RADIAL CRANE TIRES

AM 543



PRODUCT DATA SHEET



Radial



AIROMAX AM 543

RADIAL CRANE TIRES

AIROMAX AM 543 is the ideal tire for construction applications with cranes. It shows outstanding traction and high stability. As crane tires are subject to particular stress and extreme usage conditions, AIROMAX AM 543 has been designed for providing excellent heat resistance. Besides, it is suitable for all operations requiring a high level of handling.

Technologies



High Speed



All Steel

Performance



Durability



High Load Capacity



Traction

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 24"	94064502	385/95 R 24 (14.00 R 24)	TT	-	170 E	STD	53.3	14.8	24.7	163.6	30	336	10.00 W	-
Ø 25"	94064519	385/95 R 25 (14.00 R 25)	TL	-	170 E	STD	53.3	14.8	24.7	163.6	30	342	10.00/1.5	-
	94036660	445/95 R 25 (16.00 R 25)	TL	-	177 E	STD	58.3	17.1	26.4	177.2	32	445	11.25/2.0	11.00/1.7 CR ; 11.00/1.7 CRL

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference