


RIDEMAX IT 696

| | |
|---------------------|--|
| TYRE SIZE | 360/80 R 20 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 143 D ; 147 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------------|
| SW (MM) | 357 | RIM REC | 11 |
| OD (MM) | 1084 | RIM ALT | W 10 ; W 11 ; 12 ; W 12 |
| SLR (MM) | 488 | ECE | E11-106R-007845 |
| RC (MM) | 3235 | SRI | 525 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1310 | 1585 | 1885 | 2100 | 2180 | 2265 | 2480 | 2725 |
| 50 | 1415 | 1710 | 2035 | 2270 | 2360 | 2445 | 2680 | 2945 |
| 40 | 1480 | 1785 | 2125 | 2370 | 2460 | 2555 | 2800 | 3075 |
| 30 | 1570 | 1900 | 2260 | 2520 | 2620 | 2715 | 2980 | 3270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.