

AGRIMAX V- FLECTO



VF 520/85 R 42

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	180 D

UNDEFINED US STANDARD

USA CODE	94067237	RC (IN)	230.0
SW (IN)	21.1	RIM REC	DW 18 L
OD (IN)	76.8	ECE	E11-106R-007169
SLR (IN)	34.5	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	46
45	6260	7390	8510	9480	10590	11560	12690	13650	16050
FROM 40 TO 25	6880	8110	9350	10410	11640	12700	13930	14990	17640
20	7020	8280	9530	10610	11880	12960	14220	15300	17990
12	7150	8440	9720	10820	12110	13220	14490	15600	18340
5	7570	8930	10280	11450	12810	13980	15330	16490	19400
UPTO 5 CYC WITH FRONT LOADER	9630	11360	13090	14570	16300	17780	19510	20990	24690
5 HT	7020	8280	9530	10610	11880	12960	14220	15300	17990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.