

# AT 171

<b>TIRE SIZE</b>	<b>35X9 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	85 A8 ; 61 F



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	200	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	895	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	419	<b>PR</b>	6
<b>RC (MM)</b>	2670	<b>TRA CODE</b>	R1W+

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.40	1.00
40 MUD BOGGING	515	-
80 MUD BOGGING	257	-
40 CASUAL TRANSPORT	-	425
80 CASUAL TRANSPORT	-	218

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.