

FL 630 SUPER

TIRE SIZE	850/50 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	182 D



РАЗМЕРЫ US STANDARD

USA CODE	94073191	RC (IN)	192.7
SW (IN)	33.9	RIM REC	AG 28.00
OD (IN)	64.0	ECE	E11-106R-008232
SLR (IN)	28.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
45	7000	8700	9900	11430	12960	14160	15520	17050
40	7680	9560	10870	12550	14240	15550	17050	18740
30	9300	11570	13160	15200	17240	18830	20630	22670
25	10450	13010	14780	17080	19380	21150	23190	25480
15	12150	15100	17170	19840	22510	24580	26950	29610
5	13830	17210	19560	22610	25640	28000	30700	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.