

AGRIMAX V-FLECTO

TYRE SIZE	VF 710/55 R 34
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	170 D



DIMENSIONS US STANDARD

USA CODE	94513376	RIM REC	DW 25 B
SW (IN)	27.9	RIM ALT	DW 27 B
OD (IN)	65.3	ECE	E11-106R-0010831
SLR (IN)	28.6	TRA CODE	R1W
RC (IN)	193.3	TREAD DEPTH (32nd)	73.08

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29
45	5900	6860	7940	8910	9870	10820	12040
FROM 40 TO 25	6480	7540	8730	9790	10850	11900	13230
20	6600	7680	8900	9980	11060	12140	13490
12	6730	7840	9070	10170	11280	12380	13760
5	7120	8290	9600	10760	11930	13090	14550
*UPTO 5 CYC WITH FRONT LOADER	9070	10550	12210	13700	15180	16670	18520
5 HT	6600	7680	8900	9980	11060	12140	13490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.