


# EARTHMAX SR 22 AS

<b>TIRE SIZE</b>	<b>17.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HJULLASTARE / VÄGHYVLARE
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 B ; 153 A8 ; 182 A2



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94069613	<b>RIM REC</b>	14.00/1.5
<b>OD (IN)</b>	53.1	<b>TRA CODE</b>	E2/G2/L2
<b>SLR (IN)</b>	23.4	<b>STAR RATING</b>	★★/★/★★
<b>RC (IN)</b>	157.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	9650	10200	10500	11000	11400	12000	-	-	-	-
25	4080	4680	5200	5840	6400	6800	7400	8050	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	16100	16500	17100	17600	18200
MPH / PSI	94																	
30	-																	
25	-																	
5	18700																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.