

SNOW GRIP



SNOW GRIP



SNOW GRIP is specifically engineered for forklifts operating in low-temperature environments. The unique tread design features multiple gripping edges for superior grip on fresh or compact snow, resulting in excellent cornering and braking performance on icy and snowy surfaces. The dual bead construction along with the strong casing and reinforced sidewall provides higher load capacity, excellent stability and handling in lift mode in addition to a long tire life.



SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
Ø16"	7.50 - 16	TT	12	131 A2	6.0	-	31.9	0	0	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index
A2	131 lbs		

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026